Version Number 1.3 Revision Date 11/26/2019



Page 1 of 18 Print Date 12/19/2024

SAFETY DATA SHEET

GEON E6950 GRAY

Section 1. Identification		
GHS product identifier Chemical name CAS number Other means of identification	:	GEON E6950 GRAY Mixture Mixture VC10008609
Product type	-	solid
<u>Relevant identified uses of the subst</u> Product use	ance	or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	GEON Performance Solutions LLC 33587 Walker Road, Avon Lake, OH 44012
Emergency telephone number (with hours of operation)	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. All ingredients are bound in a PVC polymer matrix and potential for hazardous exposure as shipped is minimal. PVC resin is manufactured from Vinyl Chloride Monomer (VCM). PVC resin manufacturers take special efforts to strip residual VCM from their resins. Residual VCM in the resin is typically below 8.5 ppm. However, VCM is a known carcinogen. The end-user (fabricator) should take necessary precautions (mechanical ventilation, local exhaust, respiratory protection, etc.) to protect employees from exposure to any vapors or dusts that may be released during heating or fabrication. See Sections 8 and 11 for special precautions.After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	COMBUSTIBLE DUSTS CARCINOGENICITY - Category 1A

GHS label elements



Version Number 1.3	Page 2 of 18
Revision Date 11/26/2019	Print Date 12/19/2024

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	May form combustible dust concentrations in air. May cause cancer.
Precautionary statements		
General	:	Not applicable.
Prevention	:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing.
Response	:	IF exposed or concerned: Get medical attention.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	Keep container tightly closed.
Hazards not otherwise classified	:	None known. Not available.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	VC10008609

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	1 - 3	13463-67-7
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	0.3 - 1	8007-18-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Version Number 1.3 Revision Date 11/26/2019 Page 3 of 18 Print Date 12/19/2024

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Potential acute health effects





Version Number 1.3	Page 4 of 18
Revision Date 11/26/2019	Print Date 12/19/2024

Eye contact	:	Adverse symptoms may include the following: irritation redness
Inhalation	:	Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	:	No specific data.
Ingestion	:	No specific data.
Indication of immediate medica Notes to physician	al attention :	n and special treatment needed, if necessary Treat symptomatically. Contact poison treatment specialist
Notes to physician	•	immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	Use dry chemical powder. Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	:	May form explosible dust-air mixture if dispersed.
Hazardous thermal	:	May emit Hydrogen Chloride (HCl).
decomposition products		Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-

apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Version Number 1.3 Revision Date 11/26/2019 Page 5 of 18 Print Date 12/19/2024

GEON

Performance Solutions

		exposed containers cool.
Special protective equipment for	:	Fire-fighters should wear appropriate protective equipment and self-
fire-fighters		contained breathing apparatus (SCBA) with a full face-piece operated
		in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for contain	ment a	nd cleaning up
Small spill	:	Move containers from spill area. Use spark-proof tools and explosion- proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Use spark-proof tools and explosion- proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

GEON Performance Solutions LLC

SAFETY DATA SHEET GEON E6950 GRAY



Version Number 1.3	Page 6 of 18
Revision Date 11/26/2019	Print Date 12/19/2024

Protective measures Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. Advice on general occupational Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands hygiene and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. Conditions for safe storage, Store in accordance with local regulations. Store in a segregated and including any incompatibilities approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust





Version Number 1.3 Revision Date 11/26/2019 Page 7 of 18 Print Date 12/19/2024

		OCH A DEL (1002.07.20)
		OSHA PEL (1993-06-30)
		TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18)
		TWA 10 mg/m3
Nickel antimony yellow rutile (C.I.		OSHA PEL 1989 (1989-03-01)
Pigment Yellow 53)		TWA 1 mg/m3 (as Ni)
		OSHA PEL (1993-06-30)
		TWA 1 mg/m3 (as Ni)
Appropriate engineering controls	:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust
		ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. If operating conditions cause high dust concentrations to be produced, use dust goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products



Version Number 1.3	Page 8 of 18
Revision Date 11/26/2019	Print Date 12/19/2024

		if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state	:	solid [Powder.]
Color	:	GREY
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not available.
	•	
octanol/water	•	
	:	Not available.



Version Number 1.3 Revision Date 11/26/2019 Page 9 of 18 Print Date 12/19/2024

Decomposition temperature SADT Viscosity	:	Not available. Not available. Dynamic: Not available. Kinematic: Not available.
Aerosol product		
Heat of combustion	:	Not available.
Ignition distance	:	Not available.
Enclosed space ignition - Time equivalent	:	Not available.
Enclosed space ignition -	:	Not available.
Deflagration density		
Flame height	:	Not available.
Flame duration	:	Not available.

Section 10. Stability and reactivity

Reactivity		No specific test data related to reactivity available for this product or its ingredients.
Chemical stability		Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions		Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid		Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.
Incompatible materials		Avoid contact with acetal homopolymers and acetyl homopolymers during processing. Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

GEON **Performance Solutions**

SAFETY DATA SHEET GEON E6950 GRAY

Version Number 1.3 Revision Date 11/26/2019

Page 10 of 18 Print Date 12/19/2024

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Titanium dioxide				
Remarks - Oral:	No applicable toxi	city data		
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Nickel antimony yellow rutile	(C.I. Pigment Yellov	w 53)		
Remarks - Oral:	No applicable toxi	city data		
Remarks - Inhalation:	No applicable toxicity data			
Remarks - Dermal:	No applicable toxicity data			
Conclusion/Summary	: Mixtu	re.Not fully tested.		

Conclusion/Summary

Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide	Skin - Mild irritant	Human		72 hrs	-
Conclusion/Summary				<u>.</u>	
Skin	: N	lixture.Not fu	lly tested.		
Eyes	: N	lixture.Not fu	lly tested.		
Respiratory	: N	lixture.Not fu	lly tested.		
Sensitization					
Conclusion/Summary					
Skin		/lixture.Not fu			
Respiratory	: N	/lixture.Not fu	lly tested.		
Mutagenicity					
Conclusion/Summary	: N	lixture.Not fu	lly tested.		
Carcinogenicity					
Conclusion/Summary	: N	lixture.Not fu	lly tested.		

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium dioxide	-	2B	-
Nickel antimony yellow	-	1	-
rutile (C.I. Pigment Yellow			
53)			



Version Number 1.3	Page 11 of 18
Revision Date 11/26/2019	Print Date 12/19/2024

<u>Reproductive toxicity</u>		
Conclusion/Summary	:	Mixture.Not fully tested.
<u>Teratogenicity</u>		
Conclusion/Summary	:	Mixture.Not fully tested.
Specific target organ toxicity (single Not available.	exp	osure)
Specific target organ toxicity (repear Not available.	ted e	exposure)
Aspiration hazard Not available.		
Information on likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	:	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact Ingestion	:	No known significant effects or critical hazards. No known significant effects or critical hazards.
Symptoms related to the physical, ch	ıemi	cal and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: irritation, redness
Inhalation	:	Adverse symptoms may include the following: respiratory tract irritation, coughing
Skin contact Ingestion	:	No specific data. No specific data.
Delayed and immediate effects as we	ell as	chronic effects from short and long-term exposure
Short term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.

Version Number 1.3 Revision Date 11/26/2019



Page 12 of 18 Print Date 12/19/2024

Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
Carcinogenicity	:	May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.
Fertility circus	•	to known significant cricers of critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure	
Titanium dioxide			-	
	Acute LC50 > 1,000 Mg/l Marine water	Fish - Fish	96 h	
Remarks - Acute - Fish:	Acute			
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h	
Remarks - Acute - Aquatic invertebrates.:	Acute			
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h	
Remarks - Acute - Aquatic invertebrates.:	Acute			
Remarks - Acute - Aquatic plants:	No applicable toxicity data			
Remarks - Chronic - Fish:	No applicable toxicity data			



Version Number	er 1.3
Revision Date	11/26/2019

Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Nickel antimony yellow rutile			
Remarks - Acute - Fish:	No applicable toxicity data		
Remarks - Acute - Aquatic	No applicable toxicity data		
invertebrates.:			
Remarks - Acute - Aquatic	No applicable toxicity data		
plants:			
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Conclusion/Summary	: Not available.		
Persistence and degradability	<u>/</u>		
Conclusion/Summary	: Not available.		
<u>Bioaccumulative potential</u> Not available.			
Mobility in soil			
Soil/water partition coefficie (KOC)	ent : Not available.		
Other adverse effects	: No known significant effects or critical hazards.		
Section 13. Dispos	al considerations		

Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimized wherever : possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains

Version Number 1.3 Revision Date 11/26/2019 Page 14 of 18 Print Date 12/19/2024

and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Consult mode specific transport rules
International Water IMO/IMDG	:	Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations	:	United States - TSCA 12(b) - Chemical export notification: None
		of the components are listed.
		United States - TSCA 4(a) - Final Test Rules: Not listed
		United States - TSCA 4(a) - ITC Priority list: Not listed
		United States - TSCA 4(a) - Proposed test rules: Not listed
		United States - TSCA 4(f) - Priority risk review: Not listed
		United States - TSCA 5(a)2 - Final significant new use rules: Not listed
		United States - TSCA 5(a)2 - Proposed significant new use rules:
		Not listed
		United States - TSCA 5(e) - Substances consent order: Not listed
		United States - TSCA 6 - Final risk management: Not listed
		United States - TSCA 6 - Proposed risk management: Not listed
		United States - TSCA 8(a) - Chemical risk rules: Not listed
		United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
		United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined
		United States - TSCA 8(a) - Preliminary assessment report
		(PAIR): Not listed
		United States - TSCA 8(c) - Significant adverse reaction (SAR):
		Not listed
		United States - TSCA 8(d) - Health and safety studies: Not listed
		United States - EPA Clean water act (CWA) section 307 - Priority
		pollutants: Listed Nickel antimony yellow rutile (C.I. Pigment



GEON Performance Solutions LLC

SAFETY DATA SHEET GEON E6950 GRAY



Version Number 1.3	Page 15 of 18
Revision Date 11/26/2019	Print Date 12/19/2024

Yellow 53) Vinyl chloride monomer

United States - EPA Clean water act (CWA) section 311 -Hazardous substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed Listed

		1101 115004
Clean Air Act Section 112(b)	:	Listed
Hazardous Air Pollutants (HAPs)		
Clean Air Act Section 602 Class I	:	Not listed
Substances		
Clean Air Act Section 602 Class II	:	Not listed
Substances		
DEA List I Chemicals (Precursor	:	Not listed
Chemicals)		
DEA List II Chemicals (Essential	:	Not listed
Chemicals)		

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification

: COMBUSTIBLE DUSTS CARCINOGENICITY - Category 1A

Composition/information on ingredients

Name	%	Classification
Ethene, chloro-,	>= 75 - <= 90	COMBUSTIBLE DUSTS
homopolymer		
Titanium dioxide	>= 1 - <= 3	CARCINOGENICITY - Category 2
Calcium stearate	>= 1 - <= 3	COMBUSTIBLE DUSTS
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	>= 0.3 - <= 1	CARCINOGENICITY - Category 1A

<u>SARA 313</u>



Version Number	er 1.3
Revision Date	11/26/2019

Page 16 of 18 Print Date 12/19/2024

Form R - Reporting requirements

Product name	CAS number	%
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	8007-18-9	>= 0.3 - <= 1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

<u>State regulations</u> Massachusetts New York New Jersey	None of the components are listed.None of the components are listed.The following components are listed:
Pennsylvania	 Ethene, chloro-, homopolymer Calcium carbonate Titanium dioxide Nickel antimony yellow rutile (C.I. Pigment Yellow 53) The following components are listed: Calcium carbonate
	Titanium dioxide Nickel antimony yellow rutile (C.I. Pigment Yellow 53)

California Prop. 65

WARNING: This product can expose you to chemicals including Nickel antimony yellow rutile (C.I. Pigment Yellow 53), Titanium dioxide, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	-	-
Titanium dioxide	-	-

United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	At least one component is not listed in DSL but all such components are listed in NDSL.
International regulations		
Inventory list		

Version Number 1.3 Revision Date 11/26/2019



Page 17 of 18 Print Date 12/19/2024

Australia Canada	:	All components are listed or exempted. At least one component is not listed in DSL but all such components are listed in NDSL.
China	:	All components are listed or exempted.
Europe inventory	:	Not determined.
Japan	:	Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Turkey	:	Not determined.
United States	:	All components are active or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

History		
Date of printing	: 12/19/2024	
Date of issue/Date of revision	: 11/26/2019	
Date of previous issue	: 12/16/2015	
Version	: 1.3	
Key to abbreviations	ATE = Acute Toxicity Estimate	
·	BCF = Bioconcentration Factor	
	GHS = Globally Harmonized System of Classification and Labell	ing of
	Chemicals	
	IATA = International Air Transport Association	
	IBC = Intermediate Bulk Container	
	IMDG = International Maritime Dangerous Goods	
	LogPow = logarithm of the octanol/water partition coefficient	
	MARPOL = International Convention for the Prevention of Pollut	tion From
	Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = man	rine
	pollution)	

GEON Performance Solutions LLC

SAFETY DATA SHEET GEON E6950 GRAY

Version Number 1.3 Revision Date 11/26/2019 Page 18 of 18 Print Date 12/19/2024

References

UN = United Nations Not available.

:

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.

